

S-FLT Series
Intrinsic Safety Signal
Surge Protective Devices

Nanjing New Power Electric Co., Ltd.

Type	Intrinsically safe parameter
S-FLT-2-24.Ex	$U_i=30\text{ V DC}$, $I_i=50\text{ mA}$, $C_i=0\text{ }\mu\text{F}$, $L_i=0\text{ mH}$, $P_i=0.375\text{ W}$
S-FLT-3-24.Ex	$U_i=30\text{ V DC}$, $I_i=33\text{ mA}$, $C_i=0\text{ }\mu\text{F}$, $L_i=0\text{ mH}$, $P_i=0.24\text{ W}$
S-FLT-2D-24□.Ex	$U_i=30\text{ V DC}$, $I_i=25\text{ mA}$, $C_i=0\text{ }\mu\text{F}$, $L_i=0\text{ mH}$, $P_i=0.8\text{ W}$
S-FLT-□-5□.Ex	$U_i=6\text{ V DC}$, $I_i=500\text{ mA}$, $C_i=0\text{ }\mu\text{F}$, $L_i=0\text{ mH}$, $P_i=0.75\text{ W}$

conformity with the requirements on electromagnetic interference resistance of products in Class 3 industrial field atmosphere stipulate m